

EZ-LIGHT® K30L Pushbutton Indicators

Simple operator interface for
use in panels or mounted
directly on machines



Operators pick parts from bins with yellow, green or red lights and press a button to indicate the job is complete while placing parts in corresponding bin colors.



A highly visible green light indicates when it is "Okay to Enter" a workstation.



A 2-color K30L lights green to indicate which parts to pick and lights red to indicate an empty bin. A worker presses the button to verify a correct pick.

Straightforward indication solutions

Banner's K30L lighted 22 mm mount pushbuttons offer a simple operator interface solution. In applications requiring an electrically isolated light and button, the machine controller chooses when to turn the light on and off.

Your Advantages:

- Rugged, lighted operator guidance with up to three colors in one unit
- Ideal replacement of isolated dry contact pushbuttons with standard 22 mm base mount
- Long-life LEDs for low maintenance operation
- Robust IP65 rated pushbutton works well in many environments
- Fully enclosed for use in panels or mounted directly on machine
- Variety of colors available for customized indication
- Easy installation with quick disconnect models

Product Overview:

- 1-, 2- and 3-color models with up to nine single colors available
- 10 to 30V dc operation for mobile and battery-powered applications
- Light and switch are electrically isolated

**45-plus years of sensor design experience,
quality control, sales support and
cost-effective solutions**

- ▶ Banner quality products with global availability
- ▶ Rapid customization with most products shipping in 3 days or less
- ▶ Industry's largest force of application engineers to solve your toughest challenges
- ▶ More than 3,000 factory and local field representatives to serve you

www.bannerengineering.com

1.888.373.6767



more sensors, more solutions

bannerengineering.com



EZ-LIGHT® K30L Pushbutton Indicators

Dimensions

Family	Position		
	1	2	3
K30L	G	R	Y
	G = Green Y = Yellow R = Red B = Blue W = White	O = Orange V = Violet T = Turquoise M = Magenta X = No Color	

Input	Pushbutton	Connector
P	PB2	Q
P = PNP	PB2 = Dry Contact	Blank = 2 m Integral Cable Q = 4-Pin Euro Integral QD (mating cordset required) QP = 150 mm QD Pigtail (mating cordset required)



Example: K30LGRYPB2Q = K30L EZ-LIGHT with green/red/yellow indicators, PNP input, dry contact pushbutton and QD connection




for technical information

Quick-Disconnect (QD) Cordsets

4-Pin Euro Models			
	Length	Straight	Right-Angle
	1.83 m	MQDC-406	MQDC-406RA
	4.57 m	MQDC-415	MQDC-415RA
	9.14 m	MQDC-430	MQDC-430RA
5-Pin Euro Models			
	Length	Straight	Right-Angle
	1.83 m	MQDC1-506	MQDC1-506RA
	4.57 m	MQDC1-515	MQDC1-515RA
	9.14 m	MQDC1-530	MQDC1-530RA
8-Pin Euro Models			
	Length	Straight	Right-Angle
	1.83 m	MQDC2S-806	—
	4.57 m	MQDC2S-815	—
	9.14 m	MQDC2S-830	—

Hookups



Brackets

	Model
	SMB22A • Right-angle bracket with curved slot for versatile orientation • 12-ga. stainless steel

Banner offers a comprehensive selection of indicator lights including pick-to-light systems, assembly lights, call lights and verification buttons.



K30 Pick-to-Light Actuators

Compact, single-point pick-to-light solution for error-proofing and lean manufacturing.

See our catalog or visit our website for more information.